

Application No. 09/589,299
Filed: June 7, 2000
Group Art Unit: 2675

AMENDMENTS TO THE CLAIMS

Sub C1
1. (Currently Amended) A compact display device for transmitting an image to a user's eye, the display device comprising:

a head-mountable support fixture comprising an elongated member having a first end and a second end;

B1
a projection system including a display operative to provide an image, the ~~support fixture~~ projection system attached at the first end of the elongated member of the support fixture ~~to the projection system~~; and

an eyepiece assembly attached to the second end of the elongated member of the support fixture, the eyepiece assembly comprising an axial optical system;

wherein the support fixture maintains the projection system and the eyepiece assembly in alignment along an optical path through free space between the projection system and the eyepiece assembly, with the projection system disposed to transmit the image on the optical path and the eyepiece assembly disposed to receive the image from the projection system and to direct the image to the user's eye.

Application No. 09/589,299
Filed: June 7, 2000
Group Art Unit: 2675

- Plant*
2. (Original) The device of claim 1, wherein the support fixture comprises a post oriented off the optical path.
3. (Original) The device of claim 2, wherein the post is curved.
4. (Original) The device of claim 1, wherein the display comprises a liquid crystal display, an electroluminescent display, a field emission display, or a cathode ray tube.
5. (Original) The device of claim 1, wherein the projection system further comprises an illumination source.
6. (Original) The device of claim 1, wherein the eyepiece assembly comprises a reflecting surface oriented to direct the image to the user's eye and a lens.
7. (Original) The device of claim 1, wherein the eyepiece assembly allows passage of ambient light to the user's eye.
8. (Original) The device of claim 1, wherein the eyepiece assembly comprises a polarization beam-splitter coating, a

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

quarterwave plate, and a focusing mirror arranged so that polarized light from the projection system passes the beam-splitter coating and the quarterwave plate and is reflected from the focusing mirror to pass in the opposite direction through the quarterwave plate and is reflected from the beam-splitter coating toward the user's eye.

Blat
9. (Original) The device of claim 1, wherein the projection system further comprises a reflecting surface oriented to direct light from the display onto the optical path through free space.

10. (Previously Amended) The device of claim 1, wherein the projection system further comprises a lens oriented to direct light from the display onto the optical path.

11. (Original) The device of claim 1, wherein the projection system is disposed within a housing, and the housing is attached to the support fixture at the first end.

12. (Original) The device of claim 1, wherein the eyepiece assembly is disposed within a curved housing.

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

13. (Currently Amended) A compact display device for transmitting an image to a user's eye, the display device comprising:

a head-mountable support fixture comprising an elongated member having a first end and a second end;

a projection system including a display operative to provide an image, the support fixture attached at the first end to the projection system; and

an eyepiece assembly attached to the second end of the support fixture, wherein the eyepiece assembly is disposed within a hollow, transparent, spherical curved housing;

wherein the support fixture maintains the projection system and the eyepiece assembly in alignment along an optical path through free space between the projection system and the eyepiece assembly, with the projection system disposed to transmit the image on the optical path and the eyepiece assembly disposed to receive the image from the projection system and to direct the image to the user's eye.

14. (Original) The device of claim 13, wherein the eyepiece assembly further comprises a polarization beam-splitter coating, a quarterwave plate, and a focusing mirror disposed with the curved

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

housing arranged so that polarized light from the projection system passes the beam-splitter coating and the quarterwave plate and is reflected from the focusing mirror to pass in the opposite direction through the quarterwave plate and is reflected from the beam-splitter coating toward the user's eye.

15. (Original) The device of claim 14, wherein a further lens is disposed within the curved housing.

Blunt
16. (Previously Amended) The device of claim 13, wherein the eyepiece assembly further comprises a lens having an outer surface forming a part of the curved housing and an inner surface, the curvatures of the outer surface and the inner surface selected to provide a desired degree of magnification or aberration correction of light on the optical path.

17. (Original) The device of claim 13, wherein the curved housing includes an internal surface having a curvature selected to form a lens.

18. (Original) The device of claim 17, wherein the lens is a meniscus lens.

Application No. 09/589,299
Filed: June 7, 2000
Group Art Unit: 2675

19. (Original) The device of claim 13, wherein the curved housing transmits ambient light.

20. (Original) The device of claim 13, wherein the curved housing is coated with a scratch resistant coating or an antireflection coating.

21. (Currently Amended) A compact display device for transmitting an image to a user's eye, the display device comprising:

21
a head-mountable support fixture comprising an elongated member having a first end and a second end;

a projection system including a display operative to provide an image, the support fixture attached at the first end to the projection system; and

an eyepiece assembly attached to the second end of the support fixture;

wherein the support fixture maintains the projection system and the eyepiece assembly in alignment along an optical path through free space between the projection system and the eyepiece assembly, with the projection system disposed to transmit the

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

image on the optical path and the eyepiece assembly disposed to receive the image from the projection system and to direct the image to the user's eye; and

wherein the eyepiece assembly comprises a solid optical material having an external surface and an internal reflective surface, the material having an index of refraction selected so that light from the projection system incident on the external surface is refracted as the light propagates into the material and light within the material is reflected off the internal reflective surface.

22. (Original) The device of claim 21, wherein the reflective surface comprises a metal, a vacuum-deposited dielectric coating, or a holographic coating.

23. (Original) The device of claim 21, wherein the reflective surface is spherical or aspherical.

24. (Original) The device of claim 21, wherein the reflective surface is a paraboloid.

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

25. (Original) The device of claim 21, wherein the reflective surface is partially transmitting and the eyepiece assembly further includes a section adjacent the reflective surface selected to reduce refraction of ambient light passing through the reflective surface into the solid optical material.

26. (Original) The device of claim 21, wherein the solid optical material is housed within a curved housing.

B1
27. (Original) The device of claim 21, wherein the solid optical material is housed within a spherical housing.

28. (Previously Amended) The device of claims 1, 13, or 21, further comprising a housing, the projection system disposed within the housing, circuits and wiring in electrical communication with the projection system disposed within the housing, and the support fixture attached to the housing.

29. (Original) The device of claim 28, further comprising a mounting device configured to mount the housing to spectacle frames or a headband.

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

30. (Original) The device of claim 28, further including a microphone supported by the housing.

31. (Original) The device of claim 30, wherein the microphone is mounted on a boom.

32. (Original) The device of claim 28, further including an earpiece supported by the housing and operative to transmit audio output signals.

33. (Original) The device of claim 28, further comprising a boom attached to a headband, the housing attached to the boom.

34. (Original) The device of claim 33, further comprising a microphone supported by the headband.

35. (Original) The device of claim 33, further comprising an earpiece supported by the headband and operative to transmit audio output signals.

36. (Original) A cellular telephone in communication with the display device of claim 1.

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

37. (Original) A computer in communication with the display device of claim 1.

38. (Original) A personal digital assistant in communication with the display device of claim 1.

39. (Previously Added) A cellular telephone in communication with the display device of claim 13.

40. (Previously Added) A computer in communication with the display device of claim 13.

41. (Previously Added) A personal digital assistant in communication with the display device of claim 13.

42. (Previously Added) A cellular telephone in communication with the display device of claim 21.

43. (Previously Added) A computer in communication with the display device of claim 21.

-11-

WEINGARTEN, SCHURGIN,
GAGNEBIN & LEBOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313

B' concl.

Application No. 09/589,299

Filed: June 7, 2000

Group Art Unit: 2675

44. (Previously Added) A personal digital assistant in
communication with the display device of claim 21.
